

AS 30 - Heavy Cut Polish-

Product Description

Menzerna AS 30 is an effective polishing cream. AS 30 removes overspray, severe signs of use and sanding marks effectively and reliably. The polishing cream is particularly suitable for fresh, soft clear coat. AS 30 is a water based polishing cream without silicones.

<p>General information:</p> <p>Product Group: Heavy Cut</p> <p>Category: Alternative</p> <p>Cut: 10</p> <p>Gloss: 3</p> <p>Application: Paint shops</p> <p>Storage: 5- 30°C, avoid frost and direct sunlight</p> <p>Colour: White</p> <p>Volumes: 1kg pail: 14992.203.001 3kg pail: 14992.204.001 7kg pail: 14992.200.001 15kg pail: 14992.210.001 310kg pail: 14992.532.001</p>	<p>Chemical information:</p> <p>Density: 1,3-1,5 kg/l</p> <p>Viscosity: 5-15 Pas</p>
	<p>Technical information:</p> <p>Maximum abrasion: P800</p> <p>Polishing tools: Heavy Cut Foam Pad Lambswool Pad</p> <p>Speed recommendation for hard paints: Rotary: 800 rpm Orbital: lower speed range</p> <p>Pressure recommendation: High pressure</p>

Recommended Usage

- Clean surface thoroughly prior to polishing.
- Shake the bottle prior to use and apply the following quantity of the product onto the polishing pad.
Recommendation for a 40cm x 40cm area:
Pad with a diameter of 95mm: 3-4 pea-sized drops
Pad with a diameter of 150mm: 5 pea-sized drops
Pad with a diameter of 180mm: 6-7 pea-sized drops
- Use the Menzerna Heavy Cut Foam Pad or Lambswool Pad in the event of heavy signs of use. With a rotary polishing machine use our Menzerna Standard Lambswool Pad and, for an orbital polishing machine, our Menzerna Orbital Wool Pad.
- Use either a rotary or an orbital polishing machine and use the cross-coating method.
Apply strong, even pressure while polishing and extend the product with a constant low machine speed.
- At first, the polish will seem a little milky and should be worked in until only a slightly transparent/oily film is visible.

Important notice:

All the information above is based on our empirical values. Please test the use of our product yourself to determine whether it is suitable for your intended application. All matters related to the warranty and liability for this product are governed by our general selling terms and conditions, unless otherwise specified by applicable legal regulations.

How to find us:

Menzerna Polishing Compounds GmbH & Co KG
Industriestr. 25, D-76470 Ötigheim
Tel.: +49-7222-9157-0
office@menzerna.com

6. Once you have finished polishing, remove any residue with our Premium Microfiber cloth, without applying any pressure.
7. Any signs of sanding marks and use have now been removed. For an exceptionally glossy finish, now apply one of our Menzerna Medium Cut Polishes and of our Menzerna Finishes.

Important notice:

All the information above is based on our empirical values. Please test the use of our product yourself to determine whether it is suitable for your intended application. All matters related to the warranty and liability for this product are governed by our general selling terms and conditions, unless otherwise specified by applicable legal regulations.

How to find us:

Menzerna Polishing Compounds GmbH & Co KG
Industriestr. 25, D-76470 Ötigheim
Tel.: +49-7222-9157-0
office@menzerna.com