

Product Description

Menzerna Medium Cut Polish 2200 (MCP 2200) enables a high sanding effect in the medium polish process with outstanding performance in terms of gloss and sanding removal. Suitable for removing scratches, fresh paint sanding marks as well as wash and wear marks.

Cut:							6			
Gloss:								7		

Colour:	White
Density:	1,15 kg/l
Storage:	5-30 °C, avoid frost and direct sunlight
Application:	Rotative, excentric
Recommended speed:	Start: 800-1500 rpm End: 1800-2000 rpm
Maximum grinding removal:	P1000 (Lambswool) P1200 (Foam Pad)

Recommendation:
- Premium Medium Cut Foam Pad - Standard Medium Pad

Recommended Usage

1	Clean the surface thoroughly
2	Shake the bottle and apply 3 (ø95 mm) - 7 (ø180 mm) pea-sized drops of polish to the polishing pad or lambskin, depending on the pad size. Use the Medium Cut Foam Pad to remove scratches, fresh paint sanding marks, wash marks and signs of use
3.	Work in a criss-cross pattern. During polishing, apply medium, even pressure and extend the product at a constant medium speed.
4.	The polish is finished when only a slightly transparent or oily film is visible.
5.	Remove polish residues with a microfiber cloth
6.	Scratch marks, fresh paint sanding marks and traces of washing and use have now been removed. To remove holograms and achieve a perfectly glossy surface, use a Menzerna Finish product.

The Menzerna-System

	1. Heavy Cut	2. Medium Cut	3. Finish	4. Protection
Standard products	HCC 1000	MCP 2200	FF 3000	Power Lock Ultimate, Liquid Carnauba, Sealing Wax Protection
	HCC 1100	MCP 2400	SF 3500	
		MCP 2500	SFP 3800	
Premium products	SHC 300		Power Protect Ultra 2in1	
	HCC 400			
	One-Step Polish 3in1			

Packaging

Bottle, plastic, 250 ml	22771.281.001
Bottle, plastic, 1 l	22771.261.001
<i>Bulk packaging on request</i>	

For more information on the products, see:



Instagram



YouTube



Menzerna.de

Important notice:

All the information above is based on our empirical values. Please test the use of our product yourself to determine whether it is suitable for your intended application. All matters related to the warranty and liability for this product are governed by our general selling terms and conditions, unless otherwise specified by applicable legal regulations.

Copyright menzerna polishing compounds GmbH & CO KG – Entire, partially or in extracts use of this data is not permitted without agreement

Stand: TDB_MCP2200_22771_20231113_EN

Menzerna Polishing Compounds GmbH & Co KG
Industriestr. 25, D-76470 Ötigheim
Tel.: +49-7222-9157-0
office@menzerna.com