

Gelcoat Liquid Sanding - Surface Preparation -

Product Description

Menzerna Marine Gelcoat Liquid Sanding is a liquid sandpaper for marine usage, especially for gelcoat. It removes very heavy dirt and chalk. It creates the ideal basis for polishing and can also be used on places where the surface has been repaired.

<p>General Information:</p> <p>Produktgruppe: Marine</p> <p>Kategorie: Surface Preparation</p> <p>Lagerung: 5- 30°C, Frost und direkte Sonne vermeiden</p> <p>Farbe: Grau</p> <p>Gebinde: 1L: 24010.261.080</p>	<p>Chemical Information:</p> <p>Density: e.g. 1,1- 1,3 kg/l</p> <p>Viscosity: 5 – 15 Pa*s</p> <hr/> <p>Technical Information:</p> <p>Use together with: P800- P1200 Lambswool Pads or sanding fleece (by hand) Optional: Heavy Cut Foam Pad</p> <p>Rotation speed recommendation: Rotary: Lower speed range</p> <p>Pressure recommendation: High pressure</p>
--	---



Advantages

- High quality abrasive powder, very easy to process
- Even grinding pattern
- Clean finish, even on curves

Usage Recommendation

1. Before using it: clean the surface well.
2. Shake the bottle and apply the product on the pad or abrasive fleece. Please note here: the larger the pad (or abrasive fleece), the more Gelcoat Liquid Sanding you need.
3. For surface preparation, use the Menzerna Lambswool Pads (optional: Menzerna Heavy Cut Foam Pad) together with a rotary polishing machine or use a sanding fleece by hand.

Important notice:

All the information above is based on our empirical values. Please test the use of our product yourself to determine whether it is suitable for your intended application. All matters related to the warranty and liability for this product are governed by our general selling terms and conditions, unless otherwise specified by applicable legal regulations.

How to find us:

Menzerna Polishing Compounds GmbH & Co KG
Industriestr. 25, D-76470 Ötigheim
Tel.: +49-7222-9157-0
office@menzerna.com

4. If you are using a rotary polishing machine, work in a cross-pattern and if polishing by hand do it in circling movements. When using the Gelcoat Liquid Sanding, you work at low machine speed and apply strong pressure.
5. Work out the product until the dirt on the surface is removed.
6. After processing it, you can remove the residue with a microfiber cloth.
7. The surface is now prepared and the polishing marks can now be removed with the Gelcoat Premium One-Step Polish.

Menzerna Marine System

	Surface Preparation	1. Heavy Cut	2. Medium Cut	3. Finish	4. Protection
Premium System	Liquid Sanding	Premium One Step Polish		Premium Gloss	Premium Protection
Polishing Tools	Lambswool Pads	Heavy Cut Foam Pad or Lambswool Pads		Soft Cut Foam Pad	Wax Foam Pad

Important notice:

All the information above is based on our empirical values. Please test the use of our product yourself to determine whether it is suitable for your intended application. All matters related to the warranty and liability for this product are governed by our general selling terms and conditions, unless otherwise specified by applicable legal regulations.

How to find us:

Menzerna Polishing Compounds GmbH & Co KG
 Industriestr. 25, D-76470 Ötigheim
 Tel.: +49-7222-9157-0
office@menzerna.com