

Gelcoat Premium One-Step Polish - Performance Compound -

Product Description

Menzerna Gelcoat Premium One-Step Polish Gelcoat enables polishing results at the highest level, as well as time-saving work, thanks to the latest polishing technology. It polishes and creates high gloss in just one step, so it is very time-saving. Glecoat Premium One-Step is specialized for the usage in the marine sector, especially for light and dark gelcoats.

<p>General Information:</p> <p>Category: Marine</p> <p>Product Group: One-Step Produkt</p> <p>Cut: 8</p> <p>Gloss: 8</p> <p>Storage: 5- 30°C, avoid frost and direct sun</p> <p>Colour: White</p> <p>Packaging: 1L: 24011.261.080</p>	<p>Chemical Information:</p> <p>Density: e.g. 1,1 kg/l</p> <p>Viscosity: 9 – 15 Pa*s</p> <hr/> <p>Technical Information:</p> <p>Use together with: Lambswool Pads or Heavy Cut Foam Pad</p> <p>Optional: Soft Cut Foam Pad</p> <p>Rotation speed recommendation: Rotary: Start: lower speed range End: higher speed range</p> <p>Pressure recommendation: Start: high pressure on machine End: reduce pressure on machine</p>	
--	---	--

Advantages

- All polishing steps in just one product
- Fast removal of defects with the highest degree of gloss
- Easy processing even on large areas

Important notice:

All the information above is based on our empirical values. Please test the use of our product yourself to determine whether it is suitable for your intended application. All matters related to the warranty and liability for this product are governed by our general selling terms and conditions, unless otherwise specified by applicable legal regulations.

How to find us:

Menzerna Polishing Compounds GmbH & Co KG
Industriestr. 25, D-76470 Ötigheim
Tel.: +49-7222-9157-0
office@menzerna.com

Usage Recommendation

1. Before Polishing: clean the surface well.
2. Shake the bottle and pour the product onto the polishing pad. Please note: the bigger the pad, the more Gelcoat One-Step you need.
3. Use the Menzerna Heavy Cut Foam Pad or Lambswool Pads if there are signs of heavy use on the surface.
4. When using a rotary polishing machine, work in a cross-pattern.
At the beginning, run the polish at a low speed and apply strong pressure on the polishing machine. In the final steps, you increase the speed and reduce the pressure on the polishing machine.
5. Apply the Gelcoat Premium One-Step Polish until only a slightly transparent or oily film can be seen and remove polish residues with a premium microfiber cloth.
6. To increase the gloss of the surface even further, you can use the product a second time or you can apply the Gelcoat Premium Gloss afterwards. In both cases this step should be done with the Menzerna Soft Cut Foam Pad.

Menzerna Marine System

	Surface Preparation	1. Heavy Cut	2. Medium Cut	3. Finish	4. Protection
Premium System	Liquid Sanding	Premium One Step Polish		Premium Gloss	Premium Protection
Polishing Tools	Lambswool Pads	Heavy Cut Foam Pad or Lambswool Pads		Soft Cut Foam Pad	Wax Foam Pad

Important notice:

All the information above is based on our empirical values. Please test the use of our product yourself to determine whether it is suitable for your intended application. All matters related to the warranty and liability for this product are governed by our general selling terms and conditions, unless otherwise specified by applicable legal regulations.

How to find us:

Menzerna Polishing Compounds GmbH & Co KG
 Industriestr. 25, D-76470 Ötigheim
 Tel.: +49-7222-9157-0
office@menzerna.com